

PRODUCT DATA SHEET

SCL-45: Fire Resistant SCL Core Door

SPECIFICATIONS

Max Size: Singles: 4'0" x 8'0"; Pairs: 6'0" x 7'0", DE Pairs Not allowed

Transoms: Available. Contact Five Lakes for size restrictions.

Thickness: 1-3/4"

Core: 45 Minute rated fire door with NO BLOCKING REQUIRED solution!

Veneers: Any commercially available wood veneered door face. WDMA "A" Grade, Book & Running match is standard), MDO, Primed Hardboard and Decorative Plastic Laminate.

Stiles: High Density Fiber Board (HDF) with compatible veneer band, or decorative laminate.

Rails: 1-1/2" (before trim) High Density Fiber Board.

Factory Finish: UV Cured Acrylic Epoxy. Clear or stained. Five Lakes standard colors or custom color match available.

Adhesives: Door assembly – Type I
Veneers – Type II

Lites*: Many lite opening approvals are available. Contact us for the latest list of approvals.

Blocking: 40# core density eliminates the need for inner blocking for surface mounted hardware

Warranty: Five Lakes doors are warranted for interior use only. One year (standard), 2 year and 5 year are repair, replace or refund only. Life of Installation Warranty with additional benefits available.

Machining: Prefitting, beveling, lock and hinge mortise and other hardware preps available.

Fire Rating: Neutral (standard) and Positive Pressure Category B** Intertek Testing Service/Warnock Hersey international (ITS-WHI).

Standards: ANSI/WDMA I.S.1A and AWI Section 1300

*Minimum 5.5" from any edge of door including hardware cutouts, to meet labeling and warranty requirements.

**Contact Five Lakes for size restrictions

